CP-QAC-DY42L2-Q



Normal IR Dome Camera - 20 Mtr



Main Features

- \Rightarrow 1/3" Sony Super HAD CCD
- ⇒ 420 TVL Normal Resolution Camera
- \Rightarrow 0.5lux @ F1.2
- \Rightarrow 3.6 mm Fixed Lens
- \Rightarrow IR Range of 20 Mtrs with 26 LEDs
- ⇒ AGC, AWB, BLC
- \Rightarrow CE, FCC and RoHS Certified



Feature









Specification



· catalic	- Specification
Image Sensor	1/3 " Sony Super HAD CCD
Pixels	EIA/NTSC: 512 (H) X492 (V) CCIR/PAL: 512 (H) X582 (V)
Resolution	420TVL
Min. Illumination	0.5lux @F1.2
S/N Ratio	more than 48dB
Electronic Shutter	1/50(60)-1/100,000sec
Flickerless Mode	Electrical
Iris Control	Manual
Lens	3.6 mm
Gamma Correction	0.45
White Balance (AWB)	Auto
Gain Control (AGC)	Auto
Back Light Compensation	Auto
IR	26 LEDs, Upto 20 Mtrs
Sync	Internal Sync
Power Supply	DC 12V
Dimensions	73mm(h)x94mm
Weight	230g
Operating Temperature	-10~ +50℃ RH95% Max
Certifications	CE, FCC, RoHs